



Description:

LASTOIS TECHUMBRES is an elastic waterproofing based on acrylic copolymers used for decks, hips, valleys, chimneys, laylights, non-passable decks, etc.

Uses:

It is used for waterproofing decks, roofs and chimney borders. It can be reinforced with VELOAIS.

Features & benefits:

* EXCELLENT WATERPROOFING * GREAT ELASTICITY *
GREAT RESISTANCE TO BLEAKNESS *

Technical features:

Adherence	
Colour/s	black, red tile, white and grey.
Composition	Aqueous emulsion based on styrene acrylic copolymers
Density	1.32 Kg/L \pm 0.05 g/cm ³ at 20°C.
Dry upon touching	< 30 min.
Elongation until breaking point	>400%
Folding capacity under cold temper	will not crack (UNE 53,358) at -5°C
Resistance to traction	> 15 kg/cm ² (UNE 53.165)
Solid content	> 60%
Viscosity	20.000 \pm 10.000 mPa.s

Surface preparation:

The background must be dry and no trace of contaminating particles, by priming conveniently.

Clean up:

Clean using large amounts of water, when is dry remove mechanically

Consumption:

2 kg per sqm

Application

- Stir the contents of the bucket until the product is completely homogeneous.
- Apply a primer according to the nature of the support.
- In vitrified supports ANDER B should be apply as primer to open porosity and improve the adhesion of coating.
- In case of porous supports a first coat of LASTOIS TECHUMBRES diluted in water can be applied as primer.
- Once the primer dries, apply a first coat of LASTOIS TECHUMBRES in which you can place a fiber mesh as FIBRAIS.
- Should be allowed to dry well before proceeding to the application of the next coat.
- Then the next layer is applied, giving several coats until the total consumption of 2 kg/m² is get, always let every coat dry correctly before applying the next one. .
- The surface waterproofed with LASTOIS TECHUMBRES can't have standing water.

Packaging:

Available in packs of:

- 5 Kilos
- 20 Kilos

Storage:

The information provided on this technical data sheet and particularly the recommendations for the application and use of the product is based on our current knowledge and are provided in good faith, considering that the products are used, handled and stored under normal conditions and within the limits of its useful life. The possible differences between the materials, supports, and real conditions in the application site can be so important that it is no possible to establish a warranty with this document or any other information provided. The user must verify with a suitability test that the product conforms to the required use. Users should refer to the information included in the last technical data sheet edition.



PROFESSIONAL CONSTRUCTIVE SOLUTIONS

©TEAIS S.A. - All rights reserved - Avda. da Enerxía, nº 153, Pol. Ind. de Sabón - 15143 Arteixo, A Coruña
Telf.: 981 602 111 - Fax: 981 601 508 - Email: comex@teais.es



lastois techumbres

HIGH PERFORMANCE ELASTOMERIC WATERPROOFING FOR ROOFS

Edition: 5 04/2010

Technical department

It is recommended to store this product for 2 years in tightly closed original packages in a cool dry place at temperatures above 5°C.

Health and safety advice:

Consult the safety information on the label on each package, and for more information refer to the product Material Safety Data Sheet.

The information provided on this technical data sheet and particularly the recommendations for the application and use of the product is based on our current knowledge and are provided in good faith, considering that the products are used, handled and stored under normal conditions and within the limits of its useful life. The possible differences between the materials, supports, and real conditions in the application site can be so important that it is no possible to establish a warranty with this document or any other information provided. The user must verify with a suitability test that the product conforms to the required use. Users should refer to the information included in the last technical data sheet edition.



PROFESSIONAL CONSTRUCTIVE SOLUTIONS

©TEAIS S.A. - All rights reserved - Avda. da Enerxía, nº 153, Pol. Ind. de Sabón - 15143 Arteixo, A Coruña
Telf.: 981 602 111 - Fax: 981 601 508 - Email: comex@teais.es